

Schaerer Soul



Placement and connections

This leaflet provides information about space- and connection requirements to ensure safe and successful installation, and operation of your coffee machine.

The installation technician takes care of equipment installation from the wall socket(s) and the water connection point. This excludes drilling of holes in the counter or table-top to guide power cords, hoses or chutes through.

Please consult your local JDE Professional helpdesk for more information and explanation.

Please see the product brochure for more detailed information regarding range of available drinks, specifications, options and accessories.



Placement and connections
**THE BASIS FOR
GREAT COFFEE**

Schaerer Soul



Placement and connections

Please observe the guidelines to maximize safety and performance

units of measurement = mm

Please consult your local JDE Professional helpdesk for more information and explanation.

Please see the product brochure for more detailed information regarding range of available drinks, specifications, options and accessories.



⚡ POWER SUPPLY

Power consumption (rated): 3000 W (230V)
Wall outlet with earth connection
(in compliance with your local regulations),
230VAC/50Hz, 16A
Distance from machine : <1 mtr.

An additional power outlet is required for an optional cold water unit or accessories.

💧 WATER CONNECTION

(in compliance with your local regulations)
Copper piping (or similar material - approved for drinking water supply)
Non-return valve (mandatory in many countries – check your local regulations)
Water tap : 3/4" or 3/8"
Distance from machine : <1 m
Water hose length : 1000 mm
Dynamic pressure : min. 1 bar at 10 L/min
Static pressure : max. 8 bar non-shock

DIMENSIONS

H 761 mm x W 330 mm x D 600 mm

Overall space required

H 870 mm x W 530 mm x D 700 mm
(includes 100 mm at both sides of the machine for service and maintenance purpose)

Operational weight : approx. 55 kg

🔌 OTHER

- ❗ The electrical socket should not be located within a distance of 30 cm/12" or below the water connection point.
- ❗ The wall socket and water stop valve should be located in the same room as the equipment and easily accessible.
- ❗ Do not use power extension cords.
- ❗ The equipment is only suitable for indoor use. (temperature: 1 ~ 32 °C, humidity: <80% RH)
- ❗ We advice to pre-cool some milk packs for optimal milk froth adjustment at installation.

Schaerer Soul



Options and water treatment


Information concerning options,
water filters and -softeners.

units of measurement = mm


Please consult your local JDE Professional
helpdesk for more information and
explanation.

Please see the product brochure for more
detailed information regarding range of
available drinks, specifications, options
and accessories.


1



2



3



💡 EXPLANATION

1. WATER FILTER

A filter may be necessary to
optimize the water quality
The max required space is:
540 (h) x 130 (b) x 130 (d)

2. WATER SOFTENING (> 8 ° DH)

A water softener is necessary
if the water hardness exceeds 8 ° DH.
The type required depends on the
water hardness and daily number of
consumptions.

The max required space is:
580 mm (l) x 150 mm (w) x 150 mm (d)

3. WASTE PIPE

Use a 50 mm waste pipe with
siphon/waste trap (within 1 meter
distance from the machine)
for the drain hose.

Schaerer Soul





Dimensions in detail

Additional detailed information concerning dimensions.

units of measurement = mm

Please consult your local JDE Professional helpdesk for more information and explanation.
Please see the product brochure for more detailed information regarding range of available drinks, specifications, options and accessories.



Explanation

1. Additional space for (refilling) ingredient containers
2. Opening for hoses (and power cord)
3. Opening for waste bin chute
4. The optional fridge can be placed at the right or the left side, or 'under the counter'. (the latter position requires additional parts)

Schaerer Soul



Dimensions in detail

Additional detailed information concerning the 'center-milc' configuration. (one fridge flanked by 2 machines)

units of measurement = mm

Please consult your local JDE Professional helpdesk for more information and explanation.
Please see the product brochure for more detailed information regarding range of available drinks, specifications, options and accessories.

